

31040 U.S. PTO 09/783287

1 / 9 5







Fig. 3





2 / 3 5







8 / 8 5








4 / 3 5





10 Fig. 10




Fig,||

norded a continu







F19,13




7 / 9 5


万%






13 16 Fig, /6





·图 18 Fig. 18

 $H_2: O_2 = 30\% : 10\%, 25scc/min$






図-20-Fig,20




Fig. 2/







図 22 Fig, 22





Ni Ribbon (t 0.3 x 20 x 1000mm), 500°C




121-24 Fig. 24










1 4 / 3 5



1 5 / 3 5







12 30 Fig. 30

 $H_2: O_2 = 3:1$




Fig. 3)

 $H_2: O_2 = 3:1$

Ha: 100scc/min Oz: 33scc/min 620°C





Fig. 32

 $H_2: O_2 = 4:3$



1 9 / 3 5

F19.33








図 34 Fig.34









12 38 Fly 36




123-87 Fig. 37







50 30 Fig,39










2 3 / 3 5







REACTION RATE (%)







2 6 / 3 5











2 9 / 3 5




3 0 / 3 5




3 1 / 3 5

Fig. 49



8 2 / 3 5




COTTON TOTAL

3 3 / 3 5


F19.51

NATER GENERATION REACTION RATE (%)



TIMB (Er)

3 4 / 3 5







Fig.53



3 5 / 3 5